

# Inverter Module

Type WR-5073



## Important Advantages

- Switch mode inverter
- High efficiency
- Excellent dynamic regulation
- High short-circuit current
- Short circuit proof
- Compact design
- Low weight
- Deep discharge protection for battery
- Electronic bypass
- N resp. N+1 operation (optional)
- Battery filter



**GUSTAV KLEIN**  
POWER SUPPLIES - since 1948

## Technical Data Type WR-5073

Nominal power	VA	1000	1500	2500	3000
	24 V-		X		
	48 V-			X	
	60 V-	X		X	X
	110 V-	X		X	X
	220 V-	X		X	X
Input voltage tolerance	V	-15 +20% ( $\leq 48V$ -10 +20%)			
AC output voltage	V	230 $\pm$ 1%			
Output frequency	Hz	25 / 83,3 / 100 / 50 $\pm$ 0,1 %			
Distortion factor	%	$\leq 3$ (at linear load)			
Power factor		Independent, rated power is reduced, if power factor deviates from 0.8 lagging			
Efficiency	%	81 ... 91			
Overload behavior		125% for 10 min., 110% for 20 min.			
Short circuit behavior		Short circuit proof, $I_k = 3x I_N$ for 20 msec., afterwards $2x I_N$ for 5 sec.			
Audibel noise	dB(A)	$\leq 55$			
EMC		EN 61000-6-2, EN 61000-6-4			
Test voltages					
Input - output	kV AC	3,75			
Input, output – ground	kV AC	2			
Cooling		„AF“ forced convection / „AN“ natural convection According to design			
Permissible altitude		1000 m above sea level			
Permissible climate		Indoor, 3K3 according to EN 60721-3-3			
Ambient temperature	°C	-5 ... +40			
Dimensions	mm	According data sheet			
Protection class		IP20, according to EN 60529			

### Design

19"-housing or partial for mounting  
In-/Output on terminals  
Front connection  
On-off switch for inverter  
Operation mode selection switch:  
- Continuous operation  
- Standby operation  
- Start-up operation

### Functions

The inverter operates with most modern power transistors in PWM technique.  
DC in- and AC output are electrically isolated.  
An uninterrupted electronic bypass is included.

### Protection and monitoring facilities:

Overload- and short circuit protection  
Undervoltage at the input  
Over- / and undervoltage at the output

### Indications (LEDs in front panel):

- Load voltage o.k.
- DC voltage o.k.
- Load on inverter
- Load on AC mains
- Inverter fault
- Phase o.k.
- Operation

### Remote alarm (2 floating contacts):

- Inverter fault
- Inverter operation

### Options

External remote signals  
Special frequencies

11/2012

subject to change without notice

D-86956 Schongau, Im Forchet 3  
D-86952 Schongau, Postfach 1248  
Tel. (08861) 209-0, Fax (08861) 209-180



A-6401 Inzing/Tirol, Schießstand 2  
Tel. (05238) 54209-0  
Fax (05238) 54209-23

E-Mail: [vertrieb@gustav-klein.com](mailto:vertrieb@gustav-klein.com) Internet: [www.gustav-klein.com](http://www.gustav-klein.com)